



TR 317

Description

TR 317 is suitable for municipality and soil tillage operations with implement machinery, trenchers and orchard harvesters. The TR 317 tire has a large contact area which provides excellent grip and outstanding stability in any condition along with great self-cleaning properties.

UM

IS Standard

Construction

◇◇ Bias

Machinery

Agriculture ■ Implement Machinery



Version

HD

Tire Type

TL

Tyre size

18x8.50-8

LI/SS

Version	HD
Tire Type	TL
Tyre size	18x8.50-8
LI/SS	

Dimensions IS Standard

SW (IS) (mm)	215
OD (IS) (mm)	450
SLR (IS) (mm)	198
RC (IS) (mm)	1305
Rim Rec	7.00 I - 55; I - 70; I - 90

Load Capacity (IS)

km/h / bar	2.30
15	475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..