



## AGRIMAX V-FLECTO

### Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■



Version	STEEL BELTED
Tire Type	TL
Tyre size	VF520/85R50
LI/SS	177;D

## Dimensions US Standard

USA Code	94517008
SW (US) (in)	21.1
OD (US) (in)	85.0
SLR (US) (in)	38.3
RC (US) (in)	255.6
Rim Rec	DW 18 L
Rim Alt	DW 16 L
ECE	E11-106R-0011305
TRA Code	R1W

## Load Capacity (US)

mph / psi	9	12	15	17	20	23	29	35
45	6880	7900	9070	10240	11410	12590	13760	14640
from 40 to 25	7560	8690	9980	11260	12540	13830	15120	16090
20	7700	8860	10170	11490	12800	14110	15420	16410
12	7860	9030	10370	11710	13050	14380	15720	16730
5	8310	9560	10970	12390	13800	15220	16630	17700
*Upto 5 Cyc with front loader	10590	12170	13980	15770	17580	19380	21190	22530
5HT	7700	8860	10170	11490	12800	14110	15420	16410

**\*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.**

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..