



EARTHMAX SR 55

Description

EARTHMAX SR 55 is an All Steel Radial tire designed for use on wheel loaders and load haul dumps operating in the underground mining operations, and at scrap yards. Due to the excellent cut protection resulting from the EARTHMAX SR 55 tread design, EARTHMAX SR 55 is able to provide excellent performance with reduced downtime along with excellent fuel economy. Operators will also appreciate extraordinary

UM

IS Standard

Construction

 Radial

Machinery

OTR ■ Dozer



Version

CUT RESISTANT COMPOUND

Tire Type

TL

Tyre size

26.5R25

LI/SS

214;A2

Dimensions IS Standard

OD (IS) (mm)	1786
SLR (IS) (mm)	810
RC (IS) (mm)	5375
Rim Rec	22.00/3.0
TRA Code	L5S

Load Capacity (IS)

km/h / bar	07:15:00	07:00:00	07:25:00	07:50:00	08:15:00	08:00:00							
10	19000	19500	20000	20400	20800	21200							

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different L condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for errors or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without the written consent by Balkrishna Industries Ltd..