



US standard



GROWING TOGETHER

TRAC GRADER +



PRODUCT DATA SHEET



Bias

G-2



TRAC GRADER +

TRAC GRADER + (G-2) is a bias-ply tire for graders. It is an excellent choice for the budget-minded customers. The durable casing is designed to last. The self-cleaning tread design shows open lug-to-void-ratio which provides best traction in all conditions. Its "special" version is made of a special cut-and-chip-resistant compound.

Performance



Cut and Chip Resistance



Durability



Self-Cleaning



Traction

	US CODE	Tire size	Type	PR	LI/SS	Version	TRA CODE	TMPH	O.D. (In.)	O.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
															Rec.	Alt.
Ø 24"	94014545	13.00 - 24	TL	12	-	STD	G-2	-	50.4	13.4	23.6	155.2	31	152	8.00 TG SDC	9.00/1.5 (DQ); 10.00VA SDC
	94014569	13.00 - 24	TL	14	-	STD	G-2	-	50.4	13.4	23.6	155.2	31	154	8.00 TG SDC	9.00/1.5 (DQ); 10.00VA SDC
	94014583	13.00 - 24	TL	16	-	STD	G-2	-	50.4	13.4	23.6	155.2	31	161	8.00 TG SDC	9.00/1.5 (DQ); 10.00VA SDC
	94014668	13.00 - 24	TL	12	-	SPL	G-2	-	50.4	13.4	23.6	155.2	31	155	8.00 TG SDC	9.00/1.5 (DQ); 10.00VA SDC
	94014606	14.00 - 24	TL	12	-	STD	G-2	-	53.1	14.3	23.5	157.1	31	172	8.00 TG SDC	9.00/1.5 (DQ); 10.00VA SDC; 10.00WA SDC
	94014644	14.00 - 24	TL	16	-	STD	G-2	-	53.1	14.3	23.5	157.1	31	176	8.00 TG SDC	9.00/1.5 (DQ); 10.00VA SDC
	94059751	14.00 - 24	TT	12	-	STD	G-2	-	53.1	14.3	23.5	157.1	31	163	8.00 TG SDC	9.00/1.5 (DQ); 10.00VA SDC; 10.00WA SDC
	94059768	14.00 - 24	TT	16	-	STD	G-2	-	53.1	14.3	23.5	157.1	31	166	8.00 TG SDC	9.00/1.5 (DQ); 10.00VA SDC
	94014699	14.00 - 24	TL	12	-	SPL	G-2	-	53.1	14.3	23.5	157.1	31	172	8.00 TG SDC	9.00/1.5 (DQ); 10.00VA SDC; 10.00WA SDC
	94014712	14.00 - 24	TL	16	-	SPL	G-2	-	53.1	14.3	23.5	157.1	31	176	8.00 TG SDC	9.00/1.5 (DQ); 10.00VA SDC

STD: Standard - SPL: Special



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference