



EARTHMAX SR 51



Description

EARTHMAX SR 51 (L-5) is an All Steel radial tire specially designed for loaders or dozers. EARTHMAX SR 51 is ideal for severe operations requiring added cut resistance, sidewall protection and exceptional traction. The extra deep tread ensures also great stability and an extended tire life.

UM

IS Standard

Construction

 Radial

Machinery

OTR ■ Loader

Version CUT RESISTANT COMPOUND

Tire Type

TL

Tyre size

35/65R33null

LI/SS

224;A2

Dimensions IS Standard

OD (IS) (mm)	2061
SLR (IS) (mm)	872
RC (IS) (mm)	6082
Rim Rec	28.00/3.5
TRA Code	L5

Load Capacity (IS)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50
10	23600	25000	25750	26500	27250	28000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..