



EARTHMAX SR LOADER



Description

EARTHMAX SR LOADER is an OTR tire specifically designed for loading and dozing operations. Its All Steel casing along with multi-layer steel belts and a unique tread compound provide exceptional resistance to snags and punctures resulting in an extended service life. EARTHMAX SR LOADER features a unique tread pattern providing top selfcleaning properties and excellent traction on several types of terrain.

UM

IS Standard

Construction

 Radial

Machinery

OTR ■ Rigid Dump Truck

Version	CUT RESISTANT COMPOUND
Tire Type	TL
Tyre size	26.5R25
LI/SS	193;B

Dimensions IS Standard

OD (IS) (mm)	1735
SLR (IS) (mm)	763
RC (IS) (mm)	5179
Rim Rec	22.00/3.0
TRA Code	E3/L3

Load Capacity (IS)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	9500	9750	10300	10600	11200	11500
10	12850	13200	14000	14500	15000	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..