



CONTAINER KING



Description

CONTAINER KING has been designed for reach stackers in intermodal transport and logistics applications. This extraordinary tire is made of a highly wear-and-tear-resistant tread compound which minimizes tread cracks. CONTAINER KING ensures an extended tire life-cycle plus exceptional stability in lift mode.

UM

US Standard

Construction

◆ Bias

Machinery

Industrial & Construction ■ Reach Stacker

Version INDUSTRIAL

Tire Type TL

Tyre size 18.00-25

LI/SS

Dimensions US Standard

USA Code	94036516
OD (US) (in)	65.9
SLR (US) (in)	30.1
RC (US) (in)	195.1
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	IND4

Load Capacity (US)

mph / psi	145
5	50625

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..