



MULTIMAX MP 513

Description

MULTIMAX MP 513 has been designed by BKT for multi-purpose vehicles in municipality/maintenance and transport applications, for both agricultural and industrial uses. It is perfect for universal vehicles and fertilizer trucks. Thanks to the strong steel-belted nylon casing, MULTIMAX MP 513 allows to carry heavy loads at high speeds providing a comfortable driving experience. It ensures a longer service life and traction along with outstanding self-cleaning properties.



UM

IS Standard

Construction

 Radial

Machinery

Agriculture ▪ Universal Vehicle, Industrial & Construction ▪ Universal Vehicle

Version	STANDARD
Tire Type	TL
Tyre size	425/55R17MPT
LI/SS	134;G

Dimensions IS Standard

SW (IS) (mm)	421
OD (IS) (mm)	900
SLR (IS) (mm)	399
RC (IS) (mm)	2695
Rim Rec	13
Rim Alt	13.00
ECE	E4-54R-0024098

Load Capacity (IS)

km/h / bar	1.6	2.0	2.5	3.0	3.5
90	1080	1280	1550	1830	2120
65	1175	1390	1685	1990	2305
40	1245	1475	1785	2105	2440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..