



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 315 CS



PRODUCT DATA SHEET




Radial

L-3S

A2

229

Technologies



All Steel

Performance



Cut Resistance



EARTHMAX SR 315 CS

RADIAL OTR TIRES

EARTHMAX SR 315 CS L-3S is an All Steel radial tire specially designed for loaders' front axles with chains in mining operations. The special tread contour with a Chamfered Shoulder (CS), allows tire chains to be better fitted along the tread surface including the shoulder area. Its Overall Diameter after chain application matches the one of BKT EARTHMAX SR 55 L-5S fitted on the rear axle, for a close match of front and rear tires. EARTHMAX SR 315 CS is designed to eliminate the risk of front tire damage during digging operations with LHDs (Underground Load Haul Dump) and loaders.

| | Tire size | Type | TRA CODE | STAR RATING | LI/SS | Version | TKPH | O.W. | O.D. | SLR | RC | TREAD DEPTH (mm) | RIM | |
|-------|------------|------|----------|-------------|--------|---------|------|------|------|------|------|------------------|-----------|-----------|
| | | | | | | | | (mm) | (mm) | (mm) | (mm) | | Rec. | Alt. |
| | | | | | | | | | | | | | | |
| Ø 29" | 29.5 R 29 | TL | L-3S | ** | 218 A2 | CRC | - | 779 | 1891 | 842 | 5714 | 47 | 25.00/3.5 | 24.00/3.5 |
| Ø 33" | 35/65 R 33 | TL | L-3S | ** | 224 A2 | CRC | - | 880 | 1948 | 867 | 5886 | 42 | 28.00/3.5 | - |
| | 35/65 R 33 | TL | L-3S | *** | 229 A2 | CRC | - | 880 | 1948 | 867 | 5886 | 42 | 28.00/3.5 | - |

CRC: Cut Resistant Compound
(*) To be used with tire protection chain



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference