



IS standard



GROWING TOGETHER

# EM 938



PRODUCT DATA SHEET



Bias



140



# EM 938

EM 938 has been specially designed for excavators in road construction works. The tire is made of a special tread compound, which is particular resistant to cuts and snags, whilst the aggressive tread pattern provides excellent traction. EM 938 features outstanding self-cleaning properties. The strong casing provides extraordinary resistance to impacts and shocks even in heavy-duty operations.

**Performance**



Handling and Comfort



Heavy Duty



Self-Cleaning



Traction

	Tire size	Type	PR	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 20"	9.00 - 20	TT	14	140 B	STD	256	1012	481	3070	7.0	6.5 ; 7.5
	9.00 - 20	TT	16	-	STD	256	1012	481	3070	7.0	6.5 ; 7.5
	9.00 - 20	TT	18	-	STD	256	1012	481	3070	7.0	6.5 ; 7.5
<b>NEWSIZE</b>											

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.