



US standard



GROWING TOGETHER

TR 387



PRODUCT DATA SHEET



Bias



A8



160

Performance



Durability



High Load Capacity



TR 387

TR 387 is an agro-industrial tire suitable for sugar cane trailers and compactors. It features high load capacity and is available in different versions to meet specific user requirements in terms of cut and chip resistance, heavy-duty services and durability. The "dual bead" version is particularly suitable for industrial tractors and transport operations using trailers.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 24"	94066124	11.2 - 24	W 10	W 9	11.5	42.3	19.5	127.1	21	69	STD	-	TL	112 A8
	94076413	12.4 - 24	W 11	W 9; W 10	12.9	44.6	20.8	137.9	22	82	STD	8	TL	116 A8
NEWSIZE														
Ø 26"	94004980	18.4 - 26	DW 16 L	DW 15 L	19.1	57.1	25.0	163.4	30	209	STD	10	TL	138 A8
	94005000	18.4 - 26	DW 16 L	DW 15 L	19.1	57.1	25.0	163.4	30	209	STD	12	TL	142 A8
	94034086	18.4 - 26	DW 16 L	DW 15 L	19.1	57.1	25.0	163.4	30	235	HD	16	TL	148 A8
	94005048	23.1 - 26	DW 20 B	-	23.3	61.4	27.2	184.6	34	300	STD	8	TL	141 A8
	94005154	23.1 - 26	DW 20 B	-	23.3	61.4	27.2	184.6	34	336	HD	12	TL	162 A8
	94005079	23.1 - 26	DW 20 B	-	23.3	61.4	27.2	184.6	34	315	STD	12	TL	149 A8
	94005130	23.1 - 26	DW 20 B	-	23.3	61.4	27.2	184.6	34	338	DB	16	TL	155 A8
	94005116	23.1 - 26	DW 20 B	-	23.3	61.4	27.2	184.6	34	322	STD	16	TL	155 A8
	94030682	23.1 - 26	DW 20 B	-	23.3	61.4	27.2	184.6	34	353	DB HD	18	TL	157 A8
	94030941	23.1 - 26	DW 20 B	-	23.3	61.4	27.2	184.6	34	353	HD DB SPL	18	TL	157 A8
	94027767	23.1 - 26	DW 20 B	-	23.3	61.4	27.2	184.6	34	343	DB HD	18	TT	157 A8
	Ø 28"	94004959	12.4 - 28	W 11	W 9; W 10	12.8	47.2	21.7	140.8	22	94	STD	8	TL

STD: Standard - HD: Heavy Duty - DB: Dual Bead - DB HD: Dual Bead Heavy Duty - HD DB SPL: Heavy Duty Dual Bead Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



A8



Performance



Durability



High Load Capacity



	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 28"	94004966	16.9 - 28	DW 15 L	DW 14 L	17.3	55.1	24.8	160.4	26	149	STD	8	TL	131 A8
Ø 30"	94004973	16.9 - 30 (14 - 30)	DW 15 L	DW 14 L	17.3	57.1	25.8	166.1	26	157	STD	8	TL	132 A8
	94005024	18.4 - 30 (15 - 30)	DW 16 L	DW 15 L	18.7	60.2	26.7	177.6	28	191	STD	8	TL	135 A8
	94005147	18.4 - 30 (15 - 30)	DW 16 L	DW 15 L	18.7	60.2	26.8	173.0	28	209	HD	14	TT	147 A8
	94063956	620/75 - 30 (23.1 - 30)	DW 20 A; DW 20 B	-	23.8	65.9	30.3	193.3	34	371	DB	16	TL	157 A8
	94052868	620/75 - 30 (23.1 - 30)	DW 20 A; DW 20 B	-	23.8	65.9	-	-	34	381	DB HD	18	TL	160 A8
Ø 32"	94048854	24.5 - 32	DH 21	DH 21 B; DH 21 H; DH 21 HB	24.6	69.1	31.1	205.7	36	453	DB HD	16	TL	160 A8

STD: Standard - HD: Heavy Duty - DB: Dual Bead - DB HD: Dual Bead Heavy Duty



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference