



RT 747 AGRO INDUSTRIAL



Description

RT 747 AGRO INDUSTRIAL is a radial agro-industrial tire suitable for compact loaders and telehandlers. Its extra wide lugs provide excellent traction and great stability in lifting operations. It has been designed with a special cut-and-chip resistance compound that enables the tire to carry heavy loads. RT 747 AGRO INDUSTRIAL is the right answer to all general farming operations that need outstanding versatility.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ▪ Compact Loader, Industrial & Construction ▪ Compact Loader

Version	STANDARD
Tire Type	TL
Tyre size	460/70R24
LI/SS	152;A8/B

Dimensions IS Standard

SW (IS) (mm)	465
OD (IS) (mm)	1254
SLR (IS) (mm)	556
RC (IS) (mm)	3840
Rim Rec	DW 15 L
Rim Alt	DW 14 L; DW 16 L
ECE	E11-106R-004071
TRA Code	R4

Load Capacity (IS)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
50	1670	2060	2415	2805	3160	3550
40	1670	2060	2415	2805	3160	3550
30	1785	2205	2585	3000	3380	3800
25	1850	2285	2680	3115	3505	3940
10 Cyc	2505	3090	3620	4205	4740	5325
Static	3505	4325	5070	5890	6635	7455

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..