



AW 708 IND

Description

AW 708 IND has been developed for Industrial trailers. An HD version is available with a special cut-and-chip resistant compound.

UM

US Standard

Construction

◆ Bias

Machinery

Industrial & Construction ■ Trailer



Version	INDUSTRIAL
Tire Type	TL
Tyre size	400/60-15.5
LI/SS	

Dimensions US Standard

USA Code	94054213
SW (US) (in)	15.9
OD (US) (in)	34.4
SLR (US) (in)	15.0
RC (US) (in)	100.9
Rim Rec	AG 13.00
ECE	E11-106R-004254

Load Capacity (US)

mph / psi	65
5 FR	10030
15 FR	8530
20 FR	8020
25 FR	7160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..