



US standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 47 TP



PRODUCT DATA SHEET



Radial



Technologies



All Steel Radial



Extra Deep Tread

Performance



Traction



Stability



For muddy ground



High Puncture Resistance



Cut Resistance



Durability



EARTHMAX SR 47 TP

RADIAL OTR TIRES

EARTHMAX SR 47 TP (E-4) is an All-Steel radial tire specially engineered for rigid haul trucks operating in conditions requiring maximum traction and puncture resistance. The E-4 tread depth ensure long wear even on long hauls, thus reducing downtime and increasing productivity. EARTHMAX SR 47 TP is perfect for any task demanding both traction and stability particularly on muddy or slippery terrain. Available in standard and cut-resistant compounds.

	US CODE	Tire size	Type	STAR RATING	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 35"	94074204	24.0 R 35	TL	**	209 B	CRC	E-4	228	86.0	26.4	38.8	260.8	92	1858	17.00/3.5	-
	94074211	24.0 R 35	TL	**	209 B	STDC	E-4	267	86.0	26.4	38.8	260.8	92	1836	17.00/3.5	-

CRC: Cut Resistance Compound - STDC: Standard Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference