



EARTHMAX SR 53



Description

EARTHMAX SR 53 is an All Steel radial tire specially designed for loaders, dozers and low profile dump trucks (LPDT) operating in severe rocky conditions, including underground operations and scrap yards. The deep L-5 tread and the cut-resistant compound provide an extended wear life in addition to excellent traction and stability. In case of underground mine application, consult your servicing dealer or BKT representative.

UM

IS Standard

Construction

 Radial

Machinery

OTR ■ Dozer

Version	CUT RESISTANT COMPOUND
Tire Type	TL
Tyre size	26.5R25
LI/SS	202;A2

Dimensions IS Standard

OD (IS) (mm)	1788
SLR (IS) (mm)	800
RC (IS) (mm)	5376
Rim Rec	22.00/3.0
TRA Code	L5

Load Capacity (IS)

km/h / bar	4.00	4.25	4.50	4.75	5.00
10	12850	13200	14000	14500	15000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..