



US standard



GROWING TOGETHER

TR 393



PRODUCT DATA SHEET



Bias



Technologies



Reinforced Carcass



Special Compound

Performance



Excellent flotation



Reduced Soil Compaction



Self-Cleaning



Traction



TR 393

TR 393 has been specially designed for hay balers, spreaders and implement machinery on and off the road. The special tread design provides best flotation and self-cleaning properties in addition to a long service life. Thanks to its large contact area, TR 393 ensures excellent traction and minimizes soil compaction.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
\varnothing 16.1"	94053261	16.5 L - 16.1 SL	W 14 C	W 14 CH	16.5	40.4	18.1	116.8	21	114	STD	6	TL	128 B
	94075171	21.5 L - 16.1 SL	W 18 CH	W 16 CH	21.5	45.4	-	-	25	169	STD	10	TL	146 B

STD: Standard



Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference