



US standard



GROWING TOGETHER

AT 621



PRODUCT DATA SHEET



Bias



AT 621

AT 621 is suitable for backhoe loaders and compact loaders in all digging and loading operations in agriculture. The AT 621 tire features an extra deep tread which ensures great cut and chip resistance and higher durability. In addition, this BKT tire ensures great durability and self cleaning properties. AT 621 is available in several versions to meet the most differing user requirements.

Performance



Durability



Traction



Self-Cleaning



Cut and Chip Resistance

	US CODE	Tire size	Type	PR	LI/SS		Version	O.D.	S.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM		
					(In.)	(In.)		(In.)	(In.)	Rec.	Alt.					
					DW	FR										
Ø 15"	94037209	33 X 12.5 - 15	TT	8	-	-	STD	33.5	12.5	15.5	98.7	27	74	10.00 F SDC	-	
Ø 15.3"	94070619	10.0/75 - 15.3	TL	10	127 A6	-	STD	30.7	10.5	14.7	93.9	21	49	9.0	-	
Ø 16"	94051595	9.00 - 16	TT	16	137 A6	-	IND	36.4	10.2	-	-	32	77	6.50 H	6.00 G	
	94028511	12.5/70 - 16	TL	8	-	-	STD	33.7	12.4	15.2	101.7	25	71	10 LB	-	
	94054169	12.5/70 - 16	TL	14	-	-	STD	33.7	12.4	15.2	101.7	25	78	10 LB	-	
	94054350	12.5/70 - 16	TT	14	-	-	STD	33.7	12.4	15.2	101.7	25	75	10 LB	-	
Ø 18"	94035960	12.5/80 - 18	TL	12	129 A8	142 A8	SPL	38.9	12.1	17.1	114.8	35	106	W 9	11.0	
	94019731	12.5/80 - 18	TL	12	129 A8	142 A8	STD	38.9	12.1	17.1	114.8	35	104	W 9	11.0	
	94019724	12.5/80 - 18	TT	12	129 A8	142 A8	STD	38.9	12.1	17.1	114.8	35	99	W 9	11.0	
	94032730	12.5/80 - 18	TL	16	135 A8	148 A8	IND HD	38.9	12.1	17.1	114.8	35	108	W 9	11.0	
	94026258	12.5/80 - 18	TL	16	135 A8	148 A8	STD	38.9	12.1	17.1	114.8	35	98	W 9	11.0	
	94019748	12.5/80 - 18	TT	16	135 A8	148 A8	STD	38.9	12.1	17.1	114.8	35	97	W 9	11.0	
	94028542	15.5/60 - 18	TL	10	139 A2	-	-	STD	37.0	15.5	16.9	113.0	28	99	W 13	-
	94048229	15.5/60 - 18	TL	12	141 A2	-	-	STD	37.0	15.5	16.9	113.0	28	99	W 13	-
	94041602	15.5/70 - 18 (400/70 - 18)	TL	10	-	-	-	STD	40.6	15.7	18.7	122.5	28	115	W 13	-

STD: Standard - IND: Industrial - SPL: Special - IND HD: Industrial Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling



Bias



Performance



Durability



Traction



Self-Cleaning



Cut and Chip Resistance



	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	S.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM		
													Rec.	Alt.	
Ø 19.5"	94065912	385/65 D 19.5	TL	16	165 A2	STD	40.2	15.4	18.8	123.5	27	157	11.75	12.25	
	Ø 20"	94058488	12.5 - 20	TT	12	-	STD	40.9	12.8	18.9	122.2	31	141	11.0	-
		94028559	17.5/65 - 20	TL	10	-	STD	42.9	17.7	19.3	129.7	31	141	W 14 L	-
		94037216	42 X 17 - 20	TT	10	-	STD	42.2	17.0	18.9	125.9	31	149	14.00 TG SDC	-
		94060658	400/70 - 20	TL	16	152 B/ 168 A2	STD	42.9	15.9	19.4	128.8	35	154	13	12 SDC ; 13 SDC ; 14
94051526	400/70 - 20	TL	-	149 A8	STD	42.9	15.9	19.4	128.8	35	145	13	12 SDC ; 13 SDC ; 14		
Ø 24"	94035397	16.9 - 24	TL	12	149 A8	IND	51.3	17.7	23.2	153.8	37	192	DW 15 L	DW 14 L	
	94027491	17.5 L - 24	TL	8	139 A8	STD	49.4	17.7	22.0	147.7	36	165	DW 15 L	DW 14 L	
	94046232	19.5 L - 24	TL	12	151 A8	STD	51.4	19.0	23.1	155.0	37	225	DW 16 L	-	
Ø 26"	94031801	18.4 - 26	TL	12	156 A8	STD	56.1	18.9	25.6	168.8	37	254	DW 16 L	DW 15 L	
Ø 28"	94016808	16.9 - 28	TL	12	152 A8	IND	55.5	17.7	25.2	165.3	37	214	DW 15 L	DW 14 L	
	94016792	16.9 - 28	TT	12	152 A8	IND	55.5	17.7	25.2	165.3	37	206	DW 15 L	DW 14 L	
	94069675	16.9 - 28	TL	14	154 A8	IND	55.5	17.7	25.2	165.3	37	212	DW 15 L	DW 14 L	
Ø 30"	94027507	16.9 - 30	TL	12	153 A8	IND	57.5	17.7	26.4	173.1	37	224	DW 15 L	DW 14 L	

STD: Standard - IND: Industrial

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference