



MULTIMAX MP 513

Description

MULTIMAX MP 513 has been designed by BKT for multi-purpose vehicles in municipality/maintenance and transport applications, for both agricultural and industrial uses. It is perfect for universal vehicles and fertilizer trucks. Thanks to the strong steel-belted nylon casing, MULTIMAX MP 513 allows to carry heavy loads at high speeds providing a comfortable driving experience. It ensures a longer service life and traction along with outstanding self-cleaning properties.



UM

US Standard

Construction

 Radial

Machinery

Agriculture ▪ Universal Vehicle, Industrial & Construction ▪ Universal Vehicle

Version	STANDARD
Tire Type	TL
Tyre size	285/285R16MPT
LI/SS	128;G

Dimensions US Standard

USA Code	94074471
SW (US) (in)	12.0
OD (US) (in)	34.1
SLR (US) (in)	15.5
RC (US) (in)	103.0
Rim Rec	W 10
ECE	E11-54R-0020958

Load Capacity (US)

mph / psi	23	29	36	44	51	58
55	1850	2170	2600	3000	3390	3970
40	2000	2350	2800	3230	3660	4290
25	2130	2500	2990	3440	3900	4560

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..