



## EARTHMAX SR 30



### Description

EARTHMAX SR 30 (E-3/L-3) is an All Steel radial tire specifically designed and purpose-built for loaders and articulated dump trucks. It features steel belts and the rigid block pattern providing excellent stability and durability. The special cut-resistant compound makes EARTHMAX SR 30 the ideal solution for a variety of demanding working conditions.

### UM

IS Standard

### Construction

 Radial

### Machinery

OTR ■ Articulated Dump Truck

Version CUT RESISTANT COMPOUND

Tire Type TL

Tyre size 29.5R25

LI/SS 200;B

## Dimensions IS Standard

OD (IS) (mm)	1861
SLR (IS) (mm)	818
RC (IS) (mm)	5555
Rim Rec	25.00/3.5
TRA Code	E3/L3

## Load Capacity (IS)

km/h / bar	04:00:00	04:25:00	04:50:00	05:15:00	05:00:00	05:25:00								
50	11500	11800	12500	12850	13600	14000								
10	15500	16000	17000	17500	18000	-								

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different L condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for errors or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without the written consent by Balkrishna Industries Ltd..