



EARTHMAX SR 468

Description

EARTHMAX SR 468 is an All Steel truck tire. Its unique tread design with circumferential grooves and interlocking sipes for hard, rocky and tough mining applications. EARTHMAX SR 468 is designed for maximum wear resistance and heat dissipation. EARTHMAX SR 468 is a high performance tire with advanced technology to carry heavy loads, provide excellent traction and resistance to rock cuts and punctures.

UM

IS Standard

Construction

 Radial

Machinery

OTR ■ Rigid Dump Truck



Version

CUT RESISTANT COMPOUND

Tire Type

TL

Tyre size

27.00R49

LI/SS

223;B

Dimensions IS Standard

OD (IS) (mm)	2720
SLR (IS) (mm)	1235
RC (IS) (mm)	8351
Rim Rec	19.50/4.0
TRA Code	E4

Load Capacity (IS)

km/h / bar	05:00:00	05:25:00	05:50:00	06:15:00	06:00:00	06:25:00	06:50:00	07:15:00	07:00:00
50	20600	21800	22400	23000	23600	25000	25750	26500	27250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different L

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time v
or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or r
contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are prote
laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents,
format or otherwise without prior written consent by Balkrishna Industries Ltd..