



US standard



GROWING TOGETHER

PL 846



PRODUCT DATA SHEET



Bias



PL 846

PL 846 has been specially designed for implement machinery in soil tillage applications. It features excellent stability and outstanding traction as well as high cut and chip resistance. PL 846 is the ideal tire on rocky surfaces.

Performance



	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 9"	94032143	6.00 - 9	4.00 E	-	6.3	21.3	-	-	11	18	STD	10	TT	-
	94035915	6.00 - 9	4.00 E	-	6.3	21.3	-	-	11	18	STD	12	TT	-
Ø 10"	94076420	7.50 - 10 NEWSIZE	5.50 F	-	8.2	25.0	-	-	11	26	STD	12	TL	-

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference