



## XL GRIP IND3 (ECH)



### Description

XL GRIP (IND-3) is a bias-ply tire for empty container handlers in stacking and lifting applications. The tire features a strong casing, which provides great durability and as well as a high stability in lift mode.

### UM

IS Standard

### Construction

 Bias

### Machinery

Industrial & Construction ■ Empty Container Handler

Version	INDUSTRIAL
Tire Type	TT
Tyre size	12.00-24
LI/SS	

## Dimensions IS Standard

OD (IS) (mm)	1250
SLR (IS) (mm)	585
RC (IS) (mm)	3710
Rim Rec	8.5
Rim Alt	8.0
TRA Code	IND3

## Load Capacity (IS)

km/h / bar	10.00
10	10270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..