



US standard



GROWING TOGETHER

# PRO RIB F2M



PRODUCT DATA SHEET



Bias



Performance



Steering Control



# PRO RIB F2M

PRO RIB F2M is an agricultural tire for 2WD tractors in soil tillage applications. It is particularly suitable for all operations requiring a high level of handling.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 15"	94020492	9.5 L - 15 SL	7.00	8 LB	9.4	30.7	14.3	91.5	22	41	STD	8	TL	102 A8
	94020461	11 L - 15 SL	8 LB	10 LB	11.0	31.3	14.6	93.3	26	50	STD	8	TL	106 A8
Ø 16"	94055081	10.00 - 16 SL	8 LB	W 8 L	10.8	35.2	16.1	103.1	26	49	IND	8	TT	110 A8
	94020447	10.00 - 16 SL	8 LB	W 8 L	10.8	35.2	16.1	103.1	26	48	STD	8	TT	110 A8
	94027811	10.00 - 16 SL	8 LB	W 8 L	10.8	35.2	16.1	103.1	26	50	STD	8	TL	110 A8
	94027828	11.00 - 16 SL	10 LB	W 8 L; 8 LB	13.2	37.4	17.3	111.4	30	67	STD	8	TL	114 A8
	94055098	11.00 - 16 SL	10 LB	W 8 L; 8 LB	13.2	37.4	17.3	111.4	30	66	IND	8	TT	114 A8
	94020454	11.00 - 16 SL	10 LB	W 8 L; 8 LB	13.2	37.4	17.3	111.4	30	64	STD	8	TT	114 A8
Ø 16.1"	94020485	14 L - 16.1 SL	W 11 C	-	14.0	38.6	17.8	115.0	33	105	STD	12	TL	127 A8
	94074518	16.5 L - 16.1 SL	W 14 C	W 14 CH	16.9	42.2	-	-	36	136	STD	10	TL	129 A8

STD: Standard - IND: Industrial



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference