



## AGRIMAX PROCROP



### Description

AGRIMAX PROCROP is precisely engineered to meet modern farming demand in row crop and spraying applications. The advanced VF (Very High Flexion) technology allows AGRIMAX PROCROP to carry 40% more load compared to standard tires with same tire pressure. At the same time, the wide footprint of AGRIMAX PROCROP ensures low soil compaction and excellent load distribution that avoids damage to crops.

### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ Sprayer

Version	STEEL BELTED
Tire Type	TL
Tyre size	VF270/95R36
LI/SS	150;D

## Dimensions US Standard

USA Code	94511570
SW (US) (in)	11.0
OD (US) (in)	56.7
SLR (US) (in)	26.2
RC (US) (in)	173.0
Rim Rec	W9
ECE	E11-106R-0010172

## Load Capacity (US)

mph / psi	14	17	20	23	29	35	41	46	52	58
<b>45</b>	3170	3580	3970	4310	4790	5050	5530	5990	6400	6730
<b>from 40 to 25</b>	3480	3930	4370	4730	5250	5550	6070	6590	7030	7390
<b>20</b>	3550	4010	4460	4830	5360	5660	6190	6720	7170	7540
<b>12</b>	3620	4080	4550	4930	5460	5770	6310	6850	7310	7690
<b>5</b>	3830	4310	4800	5210	5780	6100	6670	7240	7730	8130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..