



MP 600

Description

MP 600 is an agro-industrial tire, suitable for municipality/maintenance operations with telehandlers and implement machinery, providing a comfortable driving experience. This tire provides good traction and excellent self-cleaning properties along with an extended product life-cycle.

UM

IS Standard

Construction

⊠ Bias

Machinery

Agriculture ▪ Implement Machinery, Industrial & Construction ▪ Telehandler



Version	STANDARD
Tire Type	TL
Tyre size	10.5-18
LI/SS	

Dimensions IS Standard

SW (IS) (mm)	272
OD (IS) (mm)	920
SLR (IS) (mm)	420
RC (IS) (mm)	2740
Rim Rec	9
Rim Alt	9 SDC
ECE	E11-106R-003581

Load Capacity (IS)

km/h / bar	3.75
40 DW	1950
50 DW	1900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..