



## EARTHMAX SR 44

### Description

EARTHMAX SR 44 (E-4) is designed for use on tipper trucks. The rugged E-4 tread pattern provides excellent traction and comfort. EARTHMAX SR 44 offers exceptional performance and extraordinary durability.

### UM

IS Standard

### Construction

☒ Radial

### Machinery

OTR ■ On/Off Truck



Version

STANDARD

Tire Type

TT

Tyre size

12.00R24

LI/SS

158;B

## Dimensions IS Standard

OD (IS) (mm)

SLR (IS) (mm)

RC (IS) (mm)

Rim Rec

Rim Alt

TRA Code

## Load Capacity (IS)

km/h / bar	04:50:00	05:15:00	05:00:00	05:25:00	05:50:00	06:15:00	06:00:00	06:25:00	06:50:00
50	3075	3150	3350	3450	3550	3650	3750	3875	4000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different L

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without notice. Balkrishna Industries Ltd. and its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The product data and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. No part of this publication may be reproduced, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or any other format without the prior written consent of Balkrishna Industries Ltd..