



COMMANDER (R)

Description

COMMANDER (R) is an agricultural tire featuring a deep tread with strong lug bases for a longer tire life-cycle. The special dual-angle lug design provides excellent traction in the fields and top self-cleaning properties. The strong casing is made of a cut-and-chip-resistant compound providing better puncture resistance together with high load capacity. COMMANDER (R) is the perfect tire for soil tillage, haulage and harvesting operations.



UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ■ Harvester

Version	STANDARD
Tire Type	TT
Tyre size	14.9-28
LI/SS	134;A6

Dimensions IS Standard

SW (IS) (mm)	388
OD (IS) (mm)	1380
SLR (IS) (mm)	642
RC (IS) (mm)	4176
Rim Rec	W 13
Rim Alt	W 11; W 12
ECE	E11-106R-005966
TRA Code	R1

Load Capacity (IS)

km/h / bar	2.30
30	2120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..