



EARTHMAX SR 32



Description

EARTHMAX SR 32 is a non-directional wide-base radial tire particularly suitable for scrapers. The tire features a strong All Steel casing and a special tread compound providing excellent cut and puncture resistance as well as durability. Additional traits are exceptional traction and flotation even during heavy-duty operations.

UM

IS Standard

Construction

 Radial

Machinery

OTR ■ Scraper

Version CUT RESISTANT COMPOUND

Tire Type TL

Tyre size 29.5R29

LI/SS 202;B

Dimensions IS Standard

OD (IS) (mm)	1980
SLR (IS) (mm)	883
RC (IS) (mm)	6009
Rim Rec	25.00/3.5
Rim Alt	24.00/3.5
TRA Code	E3

Load Capacity (IS)

km/h / bar	04:00:00	04:25:00	04:50:00	05:15:00	05:00:00	05:25:00						
50	12150	12500	13200	13600	14500	15000						

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..