



## AS 509

### Description

AS 509 has been specially designed for trailers, balers and implement machinery. It ensures high load capacity at inflation pressure protecting crops. AS 509 provides good traction and self-cleaning properties.

### UM

IS Standard

### Construction

◆ Bias

### Machinery

Agriculture ■ Baler



Version

STANDARD

Tire Type

TL

Tyre size

550/45-22.5

LI/SS

## Dimensions IS Standard

SW (IS) (mm)	540
OD (IS) (mm)	1065
SLR (IS) (mm)	479
RC (IS) (mm)	3250
Rim Rec	AG 16.00
ECE	E11-106R-006445

## Load Capacity (IS)

km/h / bar	01:50:00	02:20:00	02:10:00																
10 FR	4200	4670	5110																
20 FR	3780	4200	4600																
30 FR	3360	3735	4090																
40 FR	3000	3335	3650																
50 FR	2700	3000	3250																
10 DW	2960	3295	3605																
20 DW	2665	2965	3245																
30 DW	2370	2640	2885																
40 DW	2115	2355	2575																
50 DW	1905	2120	2300																

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by

industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make u  
of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without pr  
written consent by Balkrishna Industries Ltd..