



IS standard



GROWING TOGETHER

# EARTHMAX

RADIAL OTR TIRES

## SR 57



PRODUCT DATA SHEET



Radial

L-5

A2

204

# EARTHMAX SR 57

RADIAL OTR TIRES



EARTHMAX SR 57 is an All Steel radial tire specially engineered for loaders, dozers and utility vehicles operating in underground mines. The tire provides superior traction, stability and comfort on severe and rocky surfaces. The L-5 extra deep tread and the specially formulated UMS (underground mine service) compound provide a longer tread wear in addition to extraordinary resistance to rock cuts, and punctures.

### Technologies



All Steel



Block Pattern

### Performance



Durability



Traction



Cut Resistance



Stability

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM	
													Rec.	Alt.
Ø 15"	7.50 R 15	TT	L-5	*	-	CRC	-	223	845	-	-	46	6.00	6.50
	8.25 R 15	TT	L-5	*	-	CRC	-	240	880	-	-	47	6.50	7.00
	10.00 R 15	TT	L-5	*	-	CRC	-	278	916	-	-	48	7.50	7.00
Ø 20"	10.00 R 20	TT	L-5	*	-	CRC	-	272	1105	-	-	48	7.50	-
	12.00 R 20	TT	L-5	*	-	CRC	-	318	1180	-	-	56	8.50	-
Ø 25"	18.00 R 25	TL	L-5	**	204A2	CRC	-	515	1651	-	-	80	13.00/2.5	-

CRC: Cut Resistant Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference