



IS standard



GROWING TOGETHER

SM 54 M IND-4S



PRODUCT DATA SHEET



Bias



SM 54 M IND-4S

SM 54 M (L-4S) IND-4S is a modified version of the SM 54 pattern. The flatter tread profile results in a large contact area ensuring a longer tire life-cycle. This tire has been specially designed for empty container handlers and reach stackers in intermodal/logistics applications. SM 54 M features high stability in lift mode as well as a deep and smooth tread design, providing excellent cut resistance.

Technologies



Deep Tread

Performance



Cut and Chip Resistance




Durability



Stability

	Tire size	Type	PR	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 25"	18.00 - 25	TL	40	-	PORT IND	528	1650	750	4880	13.00/2.5	15.00/2.5
Ø 33"	18.00 - 33	TL	36	-	PORT IND	535	1895	840	5609	13.00/2.5	-
	18.00 - 33	TL	40	-	PORT IND	535	1895	840	5609	13.00/2.5	-

PORT IND: Port Industrial



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference