



## PUDDLE SPECIAL (B)

### Description

PUDDLE SPECIAL is a R-2 agricultural tire specifically designed for operations in paddy fields. The extra deep tread design along with the special lug pattern provides best grip and excellent traction even on wet and soft soil. The wide center bar provides better adaptability for road applications and provides extraordinary service performance. In addition, PUDDLE SPECIAL shows superior self-cleaning features and excellent durability.



### UM

IS Standard

### Construction

◆ Bias

### Machinery

Agriculture ■ Sprayer

Version STANDARD

Tire Type TT

Tyre size 120/90-26

LI/SS 94;A2

## Dimensions IS Standard

SW (IS) (mm)	127
OD (IS) (mm)	940
SLR (IS) (mm)	448
RC (IS) (mm)	2847
Rim Rec	4 JA
ECE	E11-106R-0011399

## Load Capacity (IS)

km/h / bar	04:00:00									
10	670									
km/h / bar	1	1.2	1.4	1.6	2.4	2.8	3.2	4	4.4	
70	2470	2755	3100	3385	3960	4360	4705	5280	5735	
from 65 to 40	2710	3025	3405	3720	4350	4790	5170	5800	6300	
30	2765	3090	3475	3795	4440	4890	5275	5920	6430	
20	2820	3150	3540	3870	4525	4985	5380	6035	6555	
10*	2980	3330	3745	4090	4785	5270	5685	6380	6930	
km/h / bar	0.6	0.8	1	1.2	1.4	1.6	2	2.4	2.8	3.2
50	685	800	920	1035	1155	1250	1385	1465	1600	1740
40	685	800	920	1035	1155	1250	1385	1465	1600	1740
30	735	860	985	1110	1235	1340	1485	1570	1715	1865
10	1025	1200	1375	1555	1730	1875	2080	2195	2400	2605
km/h / bar	0.6	0.8	1	1.2	1.4	1.6				
65	1735	2020	2300	2585	2870	3150				
50	1825	2120	2420	2715	3015	3310				
40	1900	2210	2520	2830	3140	3450				
30	1995	2320	2650	2975	3300	3625				
10 LT	2325	2705	3085	3465	3845	4225				
10HT	1995	2320	2650	2975	3300	3625				

km/h / bar	0.6	0.8	1	1.2	1.4	1.6	2	2.4		
<b>65</b>	820	960	1100	1240	1380	1500	1780	2000		
<b>50</b>	865	1010	1155	1305	1450	1575	1870	2100		
<b>40</b>	895	1050	1200	1355	1505	1635	1945	2180		
<b>30</b>	945	1105	1265	1430	1590	1725	2050	2300		
<b>10 LT</b>	1100	1290	1475	1665	1850	2010	2390	2680		
<b>10HT</b>	945	1105	1265	1430	1590	1725	2050	2300		
km/h / bar	0.6	0.8	1	1.2	1.4	1.6	2	2.4	2.8	
<b>70</b>	2545	2960	3375	3790	4145	4500	5030	5385	5915	
<b>from 65 to 40</b>	4195	4875	5560	6240	6825	7410	8290	8875	9750	
<b>30</b>	4280	4975	5670	6365	6965	7560	8455	9050	9945	
<b>20</b>	4365	5070	5780	6490	7100	7710	8620	9230	10140	
<b>10</b>	4615	5365	6115	6865	7510	8155	9120	9760	10725	
<b>*Upto 30 Cyc</b>	4765	5535	6310	7085	7750	8415	9410	10075	11070	
<b>*Upto 15 Cyc</b>	5685	6610	7535	8460	9255	10045	11235	12030	13215	
<b>*Upto 10 Cyc</b>	6230	7240	8255	9270	10140	11005	12310	13180	14480	
<b>10HT</b>	4280	4975	5670	6365	6965	7560	8455	9050	9945	
km/h / bar	0.6	0.8	1	1.2	1.4	1.6	2	2.4	2.8	
<b>70</b>	2545	2960	3375	3790	4200	4615	5090	5385	5915	
<b>from 65 to 40</b>	2795	3250	3705	4160	4615	5070	5590	5915	6500	
<b>30</b>	2855	3315	3780	4245	4710	5175	5705	6035	6630	
<b>20</b>	2910	3380	3855	4330	4800	5275	5815	6155	6760	
<b>10</b>	3075	3575	4080	4580	5080	5580	6150	6510	7150	
<b>*Upto 30 Cyc</b>	3175	3690	4210	4725	5240	5760	6350	6720	7380	

<b>*Upto</b>										
<b>15</b>	3790	4405	5025	5640	6260	6875	7580	8020	8810	
<b>Cyc</b>										
<b>*Upto</b>										
<b>10</b>	4155	4830	5505	6180	6860	7535	8305	8790	9655	
<b>Cyc</b>										
<b>10HT</b>	2855	3315	3780	4245	4710	5175	5705	6035	6630	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..