



FLOTATION 648



Description

FLOTATION 648 is particularly suitable for field and road transport as well as for spreading operations. Some sizes are designed for hay harvesters/balers. The special tread design allows for carrying very heavy loads at low pressure, guaranteeing at the same time reduced soil compaction and preventing damage to crops.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ■

| | |
|-----------|-------------|
| Version | STANDARD |
| Tyre Type | TL |
| Tyre size | 800/45-26.5 |
| LI/SS | |

Dimensions IS Standard

| | |
|----------|-----------------|
| SW (mm) | 800 |
| OD (mm) | 1393 |
| SLR (mm) | 631 |
| RC (mm) | 4185 |
| Rim Rec | AG 28.00 |
| ECE | E11-106R-004557 |

Load Capacity (IS)

| km/h / bar | 1.50 | 1.60 | 1.70 |
|------------|------|------|------|
| 10 FR | 7805 | 8105 | 8400 |
| 20 FR | 7025 | 7295 | 7560 |
| 30 FR | 6245 | 6485 | 6720 |
| 40 FR | 5575 | 5790 | 6000 |
| 50 FR | 5020 | 5210 | 5450 |
| 10 DW | 5530 | 5740 | 5950 |
| 20 DW | 4975 | 5165 | 5355 |
| 30 DW | 4425 | 4590 | 4760 |
| 40 DW | 3950 | 4100 | 4250 |
| 50 DW | 3555 | 3690 | 3875 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..