



EARTHMAX SR 22



Description

EARTHMAX SR 22 (G-2/L-2) is an All Steel radial tire specially designed for motor graders and loaders operating in extreme winter conditions on ice or snow. Operators will appreciate both excellent traction and stability provided by the large and non-directional tread design.

UM

IS Standard

Construction

 Radial

Machinery

Industrial & Construction ■ Grader,OTR ■ Loader

Version	CUT RESISTANT COMPOUND
Tire Type	TL
Tyre size	20.5R25
LI/SS	177;B

Dimensions IS Standard

OD (IS) (mm)	1490
SLR (IS) (mm)	640
RC (IS) (mm)	4315
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7
TRA Code	E2/L2

Load Capacity (IS)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50
50	5800	6150	6500	6700	6900	7300	-	-	-	-	-
10	-	-	-	-	-	9750	10000	10300	10900	11200	11500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..