



RM 500

Description

RM 500 is a steel-belted radial tire suitable for harvester implement applications. It features a strong casing and a special tread design providing high load capacity and particular cut-and-chip resistance. Thanks to its large footprint, RM 500 ensures great pressure distribution on the ground with reduced soil compaction in addition to excellent traction.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Harvester



Version	STEEL BELTED
Tire Type	TL
Tyre size	600/65R28
LI/SS	168;A8

Dimensions IS Standard

SW (IS) (mm)	590
OD (IS) (mm)	1486
SLR (IS) (mm)	640
RC (IS) (mm)	4340
Rim Rec	W 18 L
Rim Alt	W 20 L
ECE	E11-106R-005993

Load Capacity (IS)

km/h / bar	0.8	1.0	1.2	1.6	2.0
40 Free Rolling	3080	3530	3980	4820	5600
40 Drive Wheel	2200	2520	2840	3440	4000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..