



US standard



GROWING TOGETHER

TR 390



PRODUCT DATA SHEET



Bias



Performance



Durability



High Load Capacity



TR 390

TR 390 is an agro-industrial tire suitable for sugar cane trailers and compactors. TR 390 features high load capacity and increased durability. Its "dual bead HD" version is particularly suitable for industrial tractors and transport operations using trailers, whereas its "dual bead HD special" version is ideal for heavy-duty service.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 26"	94005161	23.1 - 26	DW 20 B	-	23.4	61.4	27.2	178.9	34	301	STD	8	TL	141 A8
	94005185	23.1 - 26	DW 20 B	-	23.4	61.4	27.2	178.9	34	313	STD	12	TL	149 A8
	94005222	23.1 - 26	DW 20 B	-	23.4	61.4	27.2	178.9	34	319	STD	16	TL	155 A8
	94030675	23.1 - 26	DW 20 B	-	23.4	61.4	27.2	178.9	34	353	DB HD	18	TL	157 A8
	94030958	23.1 - 26	DW 20 B	-	23.4	61.4	27.2	178.9	34	348	HD DB SPL	18	TL	157 A8
	94005239	28 L - 26	DW 25 B	DW 23 B	28.1	61.4	27.2	178.9	34	378	STD	12	TL	150 A8
	94070695	28 L - 26	DW 25 B	DW 23 B	28.1	61.4	27.2	178.9	34	417	DB	16	TL	157 A8
	94047048	28 L - 26	DW 25 B	DW 23 B	28.1	61.4	27.2	178.9	34	442	DB HD	20	TL	168 A8

DB HD: Dual Bead Heavy Duty - HD DB SPL: Heavy Duty Dual Bead Special - STD: Standard - DB: Dual Bead



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference