



IS standard



GROWING TOGETHER

# MULTIMAX

RADIAL MPT TIRES

## MP 527



PRODUCT DATA SHEET



Radial



# MULTIMAX MP 527

RADIAL MPT TIRES

MULTIMAX MP 527 is a multi-purpose radial tire designed for telehandlers and compact loaders in agro-industrial applications. The tire shows a block pattern design providing excellent traction even on the harder surfaces. The strong sidewall ensures outstanding stability in lift mode. MULTIMAX MP 527 is made of a special cut-and-chip-resistant compound providing and a long service life.

### Technologies



Block Pattern

### Performance



Stability



Traction



High Load Capacity



Cut and Chip Resistance



Hard Surfaces

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 18"	340/80 R 18 IND	143 A8/B	11 ; 11 SDC ; W 11	W 10 ; 12 ; 12 SDC	343	1001	455	3028	475	STD
	360/70 R 18 IND	142 A8/B	11	W 10 ; 11 SDC ; W 11 ; 12 ; 12 SDC	360	969	439	2887	475	STD
Ø 20"	340/80 R 20 IND	144 A8/B	11	W 10 ; 11 SDC ; W 11 ; 12 ; 12 SDC	343	1052	483	3176	500	STD
	400/70 R 20 IND (16.0/70 R 20)	149 A8/B	13	12 SDC ; 13 SDC ; 14	404	1068	494	3282	525	STD
Ø 24"	400/70 R 24 IND	152 A8/B	13	DW 12 ; DW 13 ; DW 13 L ; 13 SDC ; DW 14 L	404	1170	542	3597	575	STD
	400/80 R 24 IND	162 A8/B	DW 13	DW 12 ; DW 13 L ; DW 14 L	404	1250	578	3834	600	STD
	440/80 R 24 IND	161 A8/B	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	441	1314	601	3985	625	STD
	460/70 R 24 IND (17.5 L R 24)	159 A8/B	DW 15 L	DW 14 L ; DW 16 L	465	1254	574	3801	600	STD
	500/70 R 24 IND	164 A8/B	DW 16 L	DW 15 L ; DW 18 L	503	1310	597	4019	625	STD
Ø 26"	480/80 R 26 IND	160 A8/B	DW 15 L	DW 16 L	479	1428	642	4259	675	STD
Ø 28"	440/80 R 28 IND	156 A8/B	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	441	1415	648	4270	675	STD

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index