



AGRIMAX FORCE



Description

AGRIMAX FORCE the high-end product of BKT designed for soil tillage, haulage and harvesting high-power tractors and harvesters, ensuring efficiency. Thanks to its IF technology, this tire works with a lower inflating pressure compared to standard tires, reducing soil compaction. AGRIMAX FORCE features a deep tread pattern that provides enhanced traction, top self-cleaning and a long service life, ensuring a better economy.

UM

IS Standard

Construction

Radial

Machinery

Agriculture ■ Harvester

Version	STANDARD
Tire Type	TL
Tyre size	IF420/85R38undefined
LI/SS	155;D

Dimensions IS Standard

SW (IS) (mm)	419
OD (IS) (mm)	1670
SLR (IS) (mm)	780
RC (IS) (mm)	5017
Rim Rec	DW 14 L
Rim Alt	DW 15 L
ECE	E11-106R-004897
TRA Code	R1W

Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4					
70	1655	1900	2180	2465	2745	3030	3310	3525					
from													
65 to	1820	2090	2400	2710	3020	3330	3640	3875					
40													
30	1890	2170	2495	2815	3140	3460	3785	4030					
20	1965	2255	2590	2925	3260	3595	3930	4185					
10	2310	2650	3045	3440	3835	4225	4620	4920					
*Upto													
10													
Cyc													
with	2545	2925	3360	3790	4225	4660	5095	5425					
front													
loader													
10 HT	1890	2170	2495	2815	3140	3460	3785	4030					

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different L condition.

Printed on 22-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for errors or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy

upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or other written consent by Balkrishna Industries Ltd..