



XL GRIP (ADT)



Description

XL GRIP (ADT) is a bias-ply tire for Articulated dump trucks designed to minimize cuts and punctures in severe conditions where exceptional traction is required. These features result in an extended tire life.

UM

IS Standard

Construction

◆ Bias

Machinery

OTR ■

Version	STANDARD
Tire Type	TL
Tyre size	26.5-25
LI/SS	

Dimensions IS Standard

OD (IS) (mm)	1740
SLR (IS) (mm)	796
RC (IS) (mm)	5150
Rim Rec	22.00/3.0
TRA Code	E3

Load Capacity (IS)

km/h / bar	4.25
50	11200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..