



EM 934

Description

EM 934 has been specially designed for excavators in road construction applications. It shows excellent lateral traction as well as outstanding self-cleaning features. The unique tread compound offers cut and chip resistance whereas the strong casing provides a long service life.

UM

US Standard

Construction

 Bias

Machinery

Industrial & Construction ■ Excavator



Version	STANDARD
Tire Type	TT
Tyre size	10.00-20
LI/SS	146;B

Dimensions US Standard

USA Code	94048601
OD (US) (in)	41.7
SLR (US) (in)	19.7
RC (US) (in)	126.3
Rim Rec	7.5
Rim Alt	7.0; 8.0
TRA Code	E2

Load Capacity (US)

mph / psi	109
30	6610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..