



IS standard



GROWING TOGETHER

# EARTHMAX

RADIAL OTR TIRES

## SR 431



PRODUCT DATA SHEET



Radial



# EARTHMAX SR 431

RADIAL OTR TIRES



🇬🇧 EARTHMAX SR 431 is an All Steel tire specially designed for rigid haul trucks operating in severe mining conditions. The sizes with TRA code E-4 are recommended for surface mining operations while sizes with TRA code SH-4 are recommended for underground mining operations. The non-directional tread pattern ensures excellent traction and stability. The tire features a strong All Steel casing and a special tread compound providing extraordinary cut and chip resistance as well as a long service life even in rocky, abrasive and harsh environments.

Technologies



Performance



Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM		
												Rec.	Alt.	
Ø 25"	16.00 R 25	TL	E-4	**	177 B	CRC	166	452	1532	713	4649	45	11.25/2.0	-
	16.00 R 25	TL	E-4	**	-	CRC (UMS)	-	452	1532	713	4649	45	11.25/2.0	-
	<b>NEWSIZE</b>													
	16.00 R 25	TL	E-4	***	183 B	CRC	166	452	1532	713	4649	45	11.25/2.0	-
	18.00 R 25	TL	E-4	**	185 B	CRC	140	520	1660	760	5040	49	13.00/2.5	-
18.00 R 25	TL	SH-4	****	-	CRC	-	520	1660	760	5040	49	13.00/2.5	-	

CRC: Cut Resistance Compound - CRC: Cut Resistance Compound (UMS)

In case of underground mine application, consult your servicing dealer or BKT representative



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference