



IS standard



GROWING TOGETHER

# STEER FARM



PRODUCT DATA SHEET



Bias



Performance



Steering Control



# STEER FARM

STEER FARM has been designed for 2WD tractors in soil tillage applications, providing excellent steering performance.

	Tyre size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 14"	5.20 - 14	3.50 D	4.00 E	135	625	295	1901	STD	6	TT	75 A6
Ø 16"	6.00 - 16	4.50 E	4.00 E ; 5 K ; 5.00 F	170	740	353	2279	STD	8	TT	94 A6
	6.50 - 16	4.50 E	4.00 E ; 5.00 F ; 5.50 F	185	770	-	-	STD	8	TT	98 A6
	7.50 - 16	5.50 F	5.00 F ; 5 K ; 6.00 F	205	805	378	2451	STD	8	TT	103 A6
	7.50 - 16	5.50 F	5.00 F ; 5 K ; 6.00 F	205	805	378	2451	STD	10	TT	109 A6
Ø 20"	6.50 - 20	5.50 F	4.00 E ; 5.00 F	196	878	418	2701	STD	8	TT	101 A6

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference