



RIB 774 (A)

Description

RIB 774 (A) is a low-section implement tire offering high load capacity and a long tire life-cycle. It is suitable for hay harvesting and transport applications with balers and trailers.

UM

IS Standard

Construction

 Bias

Machinery

Agriculture ▪ Baler



Version	STANDARD
Tire Type	TL
Tyre size	200/60-14.5
LI/SS	

Dimensions IS Standard

SW (IS) (mm)	210
OD (IS) (mm)	610
SLR (IS) (mm)	288
RC (IS) (mm)	1888
Rim Rec	AG 6.75
ECE	E11-106R-003608

Load Capacity (IS)

km/h / bar	7.00
10 FR	1610
25 FR	1370
30 FR	1290
40 FR	1150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..