



AT 171

Description

AT 171 has been specifically designed for mud bogger tractors. The special directional and extra-deep tread design provides excellent traction on wet and muddy surfaces.

UM

US Standard

Construction

 Bias

Machinery

Agriculture ■ ATV



Version	STANDARD
Tire Type	TL
Tyre size	40x9-24
LI/SS	90;A8

Dimensions US Standard

USA Code	94056859
SW (US) (in)	8.3
OD (US) (in)	39.2
SLR (US) (in)	18.2
RC (US) (in)	122.5
Rim Rec	W 7
Rim Alt	W 6
TRA Code	R1W+

Load Capacity (US)

mph / psi	20	15
25 MUD BOGGING	1323	-
50 MUD BOGGING	662	-
25 CASUAL TRANSPORT	-	1070
50 CASUL TRANSPORT	-	535

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..