



US standard



GROWING TOGETHER

# XL GRIP PLUS



PRODUCT DATA SHEET



Bias



# XL GRIP PLUS

XL GRIP PLUS (L-4) has been specially designed for loaders. Its deep tread provides high cut and puncture resistance as well as an extended tire life-cycle. XL GRIP PLUS is particularly suitable for heavy-duty service.

## Technologies



Deep Tread

## Performance



Cut Resistance



Durability



Heavy Duty



Stability



Traction

	US CODE	Tire size	Type	PR	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 25"	94033331	26.5 - 25	TL	28	-	STD	L-4	-	69.9	27.2	32.1	206.8	72	1003	22.00/3.0	-
	94044856	26.5 - 25	TL	32	-	STD	L-4	-	69.9	27.2	32.1	206.8	72	1037	22.00/3.0	-
	94033584	29.5 - 25	TL	28	-	STD	L-4	-	75.4	29.9	34.5	224.8	75	1221	25.00/3.5	-
	94044863	29.5 - 25	TL	32	-	STD	L-4	-	75.4	29.9	34.5	224.8	75	1259	25.00/3.5	-
	94059577	29.5 - 25	TL	36	-	STD	L-4	-	75.4	29.9	34.5	224.8	75	1284	25.00/3.5	-
Ø 33"	94064762	35/65 - 33	TL	42	-	STD	L-4	-	81.9	35.4	-	-	79	1960	28.00/3.5	-

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference