



US standard



GROWING TOGETHER

FL 630 SUPER



PRODUCT DATA SHEET



Radial



FL 630 SUPER

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.

Technologies



Steel Belted



Reinforced Bead



High Speed

Performance



Durability



Field Protection



Excellent flotation



Self-Cleaning



Traction

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 22.5"	94059539	560/60 R 22.5	165 D	AG 16.00	17.00 ; 20.00	21.4	49.0	21.6	149.0	31	259	STD
	94042166	560/60 R 22.5	161 D	AG 16.00	17.00 ; 20.00	21.4	49.0	21.6	149.0	31	259	STD
	94045037	580/65 R 22.5	166 D	AG 18.00	AG 16.00 ; AG 17.00 ; AG 20.00	22.7	52.2	23.4	159.8	31	281	STD
	94073221	580/65 R 22.5	174 D	AG 18.00	AG 16.00 ; AG 17.00 ; AG 20.00	22.9	52.2	23.4	159.8	31	313	STD
	94060900	600/50 R 22.5	159 D	AG 20.00	-	24.1	46.1	20.4	139.1	31	256	STD
	94056149	600/55 R 22.5	162 D	AG 20.00	-	23.4	48.5	22.0	147.9	31	273	STD
Ø 26.5"	94040476	600/55 R 26.5	165 D	AG 20.00	-	24.1	52.5	23.9	160.6	31	309	SB
	94048946	600/55 R 26.5	177 D	AG 20.00	-	24.1	52.5	23.8	161.6	31	321	HD
	94038855	650/55 R 26.5	169 D	AG 20.00	-	25.4	54.7	24.7	167.6	31	336	STD
	94048953	650/55 R 26.5	178 D	AG 20.00	-	25.4	54.7	24.7	169.0	31	348	HD
	94045587	650/65 R 26.5	174 D	AG 20.00	-	25.4	59.8	26.9	183.2	31	375	STD
	94053445	710/50 R 26.5	170 D	AG 24.00	AG 20.00	28.6	54.4	24.6	166.8	31	353	STD
	94046096	750/45 R 26.5	170 D	AG 24.00	-	29.7	53.1	23.9	163.3	32	377	STD
	94042135	750/60 R 26.5	180 D	AG 24.00	-	29.7	62.0	27.3	189.0	32	467	STD

STD: Standard - HD: Heavy Duty - SB: Steel Belted

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Radial



Technologies



Steel Belted



Reinforced Bead



High Speed

Performance



Durability



Field Protection



Excellent flotation



Self-Cleaning



Traction



	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 30.5"	94045594	650/65 R 30.5	176 D	AG 20.00	-	25.4	63.8	28.9	195.9	31	413	STD
	94506293	710/50 R 30.5 NEWSIZE	173 D	AG 20.00	AG 24.00	27.0	58.5	26.6	179.1	31	400	SB
	94041190	750/60 R 30.5	181 D	AG 24.00	-	29.7	65.9	29.4	201.4	32	512	STD
	94073191	850/50 R 30.5	182 D	AG 28.00	-	33.9	64.0	28.4	192.7	32	566	STD

STD: Standard - SB: Steel Belted



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference