



FL 695

Description

FL 695 has been specifically designed for trailers in construction and farming transport applications with a unique center-block tread pattern. Thanks to its strong casing, FL 695 can carry heavy loads maintaining stability in all conditions. Its deep tread ensures optimal self-cleaning during on-and-off-the-road applications. Multiple steel-cord layers reinforce this pattern against punctures.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Trailer, Industrial & Construction ■ Trailer



Version STEEL BELTED

Tire Type TL

Tyre size 600/55R26.5

LI/SS 173;D

Dimensions US Standard

USA Code	94072897
SW (US) (in)	23.3
OD (US) (in)	52.6
SLR (US) (in)	24.4
RC (US) (in)	161.0
Rim Rec	AG20.00
ECE	E11-106R-007937

Load Capacity (US)

mph / psi	12	17	23	29	35	41	46	52	58	65	73	80	87
40	--	--	--	6450	7450	8450	9310	10170	11180	11890	12610	13470	14330
30	--	--	--	7800	9020	10240	11280	12310	13520	14400	15270	16300	17340
25	--	6440	7990	8770	10140	11510	12680	13840	15210	16180	17150	18320	19490
20	5410	7140	8870	9740	11250	12780	14060	15370	16890	17970	19050	20350	21640
15	5670	7470	9290	10200	11780	13360	14730	16080	17670	18790	19930	21280	22640
10	5920	7800	9700	10650	12300	13950	15380	16790	18450	19630	20810	22230	23640
5	6450	8520	10580	11610	13410	15220	16770	18320	20130	21420	22710	24250	25790

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..