



## TR 136

### Description

TR 136 has been developed by BKT to equip tractors and trailers in soil tillage and haulage operations. This tire provides improved traction in all working conditions along with best cut and chip resistance to reduce machine downtime and increase your productivity. Thanks to the increased number of lugs, TR 136 provides outstanding traction even at high loads.

### UM

IS Standard

### Construction

 Bias

### Machinery

Agriculture ■ Tractor



Version	SPECIAL
Tire Type	TL
Tyre size	16.9-30
LI/SS	143;A6

## Dimensions IS Standard

SW (IS) (mm)	429
OD (IS) (mm)	1485
SLR (IS) (mm)	687
RC (IS) (mm)	4523
Rim Rec	W 15 L
Rim Alt	W 14 L
TRA Code	R1

## Load Capacity (IS)

km/h / bar	2.40
30	2725

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..