



US standard



GROWING TOGETHER

SUPER GRADER



PRODUCT DATA SHEET



Bias

G-2



SUPER GRADER

USA SUPER GRADER (G-2) is a bias tire particularly designed for graders. It shows excellent traction and self-cleaning features. SUPER GRADER is made of a special compound which enables an extended tire life-cycle and heavy-duty service.

Technologies



Special Compound

Performance



Durability



Heavy Duty



Self-Cleaning



Traction

| | US CODE | Tire size | Type | PR | LI/SS | Version | TRA CODE | TMPH | O.D. | O.W. | SLR | RC | TREAD DEPTH (32nds) | TIRE WEIGHT (lbs) | RIM | |
|-------|----------|------------|------|----|-------|---------|----------|------|-------|-------|-------|-------|---------------------|-------------------|--------------|---|
| | | | | | | | | | (In.) | (In.) | (In.) | (In.) | | | Rec. | Alt. |
| Ø 24" | 94014477 | 13.00 - 24 | TL | 12 | - | STD | G-2 | - | 50.2 | 13.4 | 23.1 | 149.6 | 32 | 159 | 8.00 TG SDC | 9.00/1.5 (DC); 10.00/VA SDC |
| | 94035335 | 13.00 - 24 | TL | 16 | - | STD | G-2 | - | 50.2 | 13.4 | 23.1 | 149.6 | 32 | 164 | 8.00 TG SDC | 9.00/1.5 (DC); 10.00/VA SDC |
| | 94062935 | 13.00 - 24 | TT | 12 | - | STD | G-2 | - | 50.2 | 13.4 | 23.1 | 149.6 | 32 | 151 | 8.00 TG SDC | 9.00/1.5 (DC); 10.00/VA SDC |
| | 94062942 | 13.00 - 24 | TT | 16 | - | STD | G-2 | - | 50.2 | 13.4 | 23.1 | 149.6 | 32 | 157 | 8.00 TG SDC | 9.00/1.5 (DC); 10.00/VA SDC |
| | 94062973 | 14.00 - 24 | TT | 12 | - | STD | G-2 | - | 52.6 | 14.3 | 24.3 | 158.9 | 32 | 175 | 8.00 TG SDC | 9.00/1.5 (DC); 10.00/VA SDC; 10.00/WA SDC |
| | 94062980 | 14.00 - 24 | TT | 16 | - | STD | G-2 | - | 52.6 | 14.3 | 24.3 | 158.9 | 32 | 181 | 8.00 TG SDC | 9.00/1.5 (DC); 10.00/VA SDC |
| | 94014507 | 14.00 - 24 | TL | 12 | - | STD | G-2 | - | 52.6 | 14.3 | 24.3 | 158.9 | 32 | 183 | 8.00 TG SDC | 9.00/1.5 (DC); 10.00/VA SDC; 10.00/WA SDC |
| | 94014514 | 14.00 - 24 | TL | 16 | - | STD | G-2 | - | 52.6 | 14.3 | 24.3 | 158.9 | 32 | 187 | 8.00 TG SDC | 9.00/1.5 (DC); 10.00/VA SDC |
| | 94035441 | 16.00 - 24 | TL | 16 | - | STD | G-2 | - | 57.1 | 16.9 | 25.4 | 169.6 | 37 | 282 | 10.00 VA SDC | - |

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference