



AGRIMAX V-FLECTO

Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ High-Power Tractor



Version	STANDARD
Tire Type	TL
Tyre size	600/60R28
LI/SS	163;D

Dimensions US Standard

USA Code	94515059
SW (US) (in)	23.1
OD (US) (in)	56.7
SLR (US) (in)	24.9
RC (US) (in)	170.2
Rim Rec	DW 20 B
Rim Alt	DW 18 L
ECE	E11-106R-0011589
TRA Code	R1W

Load Capacity (US)

mph / psi	9	12	15	17	20	23	35
45	4510	5190	5970	6660	7440	8120	9780
from 40 to 25	4950	5700	6560	7310	8170	8930	10750
20	5050	5810	6690	7450	8330	9100	10960
12	5150	5930	6820	7610	8500	9280	11180
5	5450	6270	7210	8040	8980	9810	11820
Upto 5 Cyc with front loader	6920	7980	9180	10240	11440	12490	15050
5 HT	5050	5810	6690	7450	8330	9100	10960

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..